

Bag In Box Topper

CLEANING INSTRUCTIONS



Do not clean heated surfaces until they have been given sufficient time to cool. Failure to do so may result in serious burns.

Cretors recommends the Bag In Box Topper Cleaning System Kit. The cleaning procedure is necessary to maintain optimal performance of the BIB Topper System. This procedure should be performed periodically. Cleaning requirements will vary depending upon the types of topping oils being used.



Failure to complete the periodic cleaning will result in a complete clog. This may require that the unit be completely dis-assembled for cleaning.

1. Preparation

- a. Turn 'ON' Rocker Switch one hour before cleaning unit to allow system to heat.
- b. Fill cleaning tank to the $\frac{1}{4}$ line with hot tap water (135° F) (60°C).
- c. Pump to 40 PSI (see PSI numbers indicated on the side of a small rising cap valve at top of bottle).

2. Topper Cleaning

- a. Place bucket under dispensing head.
- b. Disengage bag connector from bag
- c. Disengage the hose leading from the bag to the pump at the base of the pump using the quick connect. Unplug black heater cord.



Oil may drain from hose when disconnected.

- d. Attach hose from BIB Cleaning System to base of BIB unit.
- e. Depress and lock the hand valve to flush hot water through the system.
- f. Push topping Dispense Button to begin cleaning process. Oil and water will begin discharging from dispensing head. Allow the system to drain all water and air from tank. (approximately 30 seconds)
- g. If oil and water do not begin to discharge from dispensing head, the pump is completely clogged. To loosen the clog, do the following:
 - 1.) Using a hair dryer, blow hot air onto all the joints around the pump mechanism.
- h. Disconnect cleaning tank upon completion.

3. Hose Cleaning

- a. Remove black heater cord from hose before cleaning.



Failure to do so will result in damage to the heater cord.

- b. Take unconnected portion of hose with connector to sink to drain. Allow hot water to run in bag connector area for cleaning.
- c. After rinsing, re-insert black heater cord back between metal and hose. For proper connection, plug must be opposite the plastic bag connector.

4. Reconnect Topper

- a. Reconnect hose onto bag/box using plastic connector.
- b. Hold hose below connection level to allow oil to fill hose. Oil will begin to flow back into hose upon proper connection.
- c. Attach loose end of hose back to base of pump after hose is full of oil.
- d. Plug heated cord back into unit.
- e. Depress the dispensing head "Press to Pump" button for about one minute until oil runs freely from system. Allow oil to flush any remaining water from the system prior to removing bucket.
- f. Clean off all areas. System is ready for customer use.



C. CRETORS AND COMPANY
3243 N. CALIFORNIA AVENUE
CHICAGO, IL 60618
PHONE (773) 588-1690, (800) 228-1885, FAX (773) 588-2171
WEB SITE: <http://www.cretors.com> Email: postmaster@cretors.com