

Kegarators / Back Bar Cooler



FBB/FDD Series FBB-24 • FDD-24 • FDD-24S
FBB-24S • FBB-24G • FBB-24SG

Standard Features

Our Single door units are designed with **durability and strength** to handle the abuse of a portable unit.

Refrigeration system is a free flowing air system throughout the box to ensure **“ICE COLD”** products at all times.

Heavy duty 18 gauges **stainless steel** top, durable stainless steel covered corner floor, stainless steel glass rail and reinforced bottom door frame to protect your long term investment.

Incandescent **interior light** underneath the mullion to protect itself from normal operations. (FBB models only)

NSF approved for bottle and pre packed goods.

FDD-24(S) single keg units are rear breathing with internal drain, internal CO2 chain harness and with knockout plate for external CO2 connection.

FBB-24(S)(G) single door units are rear breathing with epoxy coated shelves.

Item # _____



FDD-24 (S)



FBB-24 (S)(G)

Options & Accessories

□ 220 volts / 50 cycles / 1 phase



* Conforms to UL & NSF-7 standards

ISO -9001

Model	Doors	Capacity (12oz.cans)	Barrel	Shelves	HP	Voltage	Amps	Cord length	Cabinet Dimensions (L D H*)			Shipping (Wt. Cubes)	
FBB-24 (S)(G)	1	415	1	2	2.7	1/6	115	5-15P	23 3/4" (603 mm)	30 1/2" (775 mm)	40 1/8" (1038 mm)	165" (75 kg)	23 (0.65 m ³)
FDD-24 (S)	1	-	1	0	2.7	1/6	115	5-15P	23 3/4" (603 mm)	30 1/2" (775 mm)	40 1/8" (1038 mm)	165" (75 kg)	23 (0.65 m ³)

Specifications FBB/FDD Series

Construction

Heavy duty stainless steel top, 18 gauge. Black vinyl front, sides and back. (S) Model's have stainless steel front, sides and back. Interior constructed of heavy duty galvanized steel walls with coved corner NSF approved stainless steel floor.

Door is comprised of heavy duty black vinyl steel. (S) Models are stainless steel. (G) Models are a dual pane glass with black frame, (SG) Models are a dual pane glass with aluminum frame.

Provided with locks per door, magnetic door gaskets, removable without tools. Door openings have a plastic breaker strips to retard condensate formation. Unit comes complete with a 1-1/2" CFC-Free polyurethane insulation, foamed in place.

Refrigeration system

Self contained capillary tube system using environmentally friendly (CFC Free) R-134a refrigerant. Rear breathing compressor. Evaporator coil is mounted to interior top of the unit. Large fan motor and fan blades for greater air flow. Automatic condensate evaporator, no drain connection required.

Evaporator condensate has been plumbed to a condensate pan located in the compressor housing.

Access for the condensing unit behind the back grill, slides out for easy cleaning and maintenance.

Cabinets are designed to maintain temperatures between 33° F to 38° F in the interior cabinet.

Lights

Interior fluorescent light underneath the mullion. (FBB models only)

Others

Unit is supplied standard with an 8' cord and plug (Nema 5-15p).

Warranty

One year labor and parts warranty. 5 year compressor warranty (Continental U.S.A. & Canada only).

