

| Project: | |
|-----------|-----------|
| Location: | |
| Item #: | Quantity: |
| Model #: | |

MODEL: VAR 1500 H **DISPLAY CASES - Gelato Curved Glass**



General Strengths

- Sanitation. The interior cabinet is built with rounded corners (extensive radius for easy cleaning). Quick ability to take off shelves and slides for interior cleaning. Each cabinet has a drain at the bottom of the unit. When cleaning the unit make sure the drain hose is routed to a floor drain.
- Control systems. Higher precision in managing temperature settings. Greater ability to adjust temperature ranges as per the end user's requirement.
- Modular Line. Closed and open angles to adapt the elements to a determinated space. Designed for gelatos.

- 100% Tested. All condenser units are tested 100%, in helium chambers to refrigerant leak detections.
- Certified. Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7. AENOR audited and certified by internationally recognized firm. ISO 9001:2008 (Quality); ISO 14001:2004 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety)
- Lighting. Interior cabinet includes LED lighting, for brighter lighting and energy efficiency. LED saves 90% more energy compared to traditional fluorescent bulbs. Increases product visibility considerably.

| MODELS | | Dimensions inches) (mn | | Nº Dana | Ref. | Ref. Weight | Temp. Range | Capacity (Cu. Ft.) | Cond. Unit. | Case | Crated Weight |
|--------------|--------|---------------------------|--------|------------|-------|----------------|----------------|-----------------------|----------------|------------|------------------|
| | W | D | Н | Pans | | (Lbs.) (gr.) | (°F) (°C) | (L) | H.P. | Amps | (Lbs.) (Kg.) |
| VAR 1500 H | 59-7/8 | 45 | 55-3/8 | 16 R4 | R404A | 1.0 + 1.21 | -5°F/+5°F | 3.95 | 1+1/2 | 6.1 (230V) | 660 |
| VAIX 1300 II | 1445 | 1160 | 1400 | | | 450 + 550 | -18ºC/-15ºC | 112 | | 5.4 (115V) | 300 |

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE







| Project: | |
|-----------|-----------|
| Location: | |
| Item #: | Quantity: |
| Model #: | |

MODEL: VAR 1500 H

DISPLAY CASES – Gelato Curved Glass

STANDARD FEATURES

Exterior

- Laminated plate.
- ABS thermoformed sides.
- Compac worktop.
- Liftable curved tempered glass.
- Night curtain standard in the back.
- Decoration standard: White or Black.

Interior

- AISI 304 Stainless Steel.
- Structure for glasses support of silver anodized Aluminium.
- LED Lighting.

Insulation

High density CFC free Polyurethane foam.

OPTIONAL FEATURES

- ✓ Electrical connection is 220-230 V / 1ph / 50 Hz (plug type varies).
- ✓ Decoration: Red / Blue / Orange / Green.
- ✓ Customizable decoration for lower front and side panels.

Pans

- (16) Stainless Steel pans. Pans included.
- Dimensions: 14-1/5"x6-1/5"x6" (360x165x170 mm).

Refrigeration

- Temperature and defrost regulated by a digital controller.
- Ventilated condensation system.
- Evaporative pan Stainless Steel.
- Evaporator coil coated with anti-corrosion material.
- Recommendation: Case engineered to operate at 75°F and 60% RH.

Electrical

- Cord included.
- Electrical connection is 115V / 1ph / 60 Hz (digital control).
- Electrical connection is 230V / 1ph / 60 Hz (compressor).
- ETL Listed to UL471 Standard and Sanitation classified to NSF7.

PLAN VIEW

PLAN VIEW RIGHT VIEW ELEVATION 45" (1150 mm) 59-7/8" (1445 mm) 55-1/2" (1400 mm) 55 1/2" (1400 mm)

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

