

APRON FRONT BATH
AK-603216, AK-603014

Features

- SONG cast iron
- Acid-resistant enamel finish
- Anti Slip finish in basin area
- ADA compliant when installed per Section 607
- Integral Apron
- Left or right drain

Codes/Standards Compliance

Specified model meets or exceeds the following specifications:

- American Standard ASME A112.19.1M-2004
Enameled Cast Iron Plumbing Fixtures
- American Standard ICC/ANSI A117.1-2003
- British Standard BS EN 232-2003 Baths
- Canadian Standard CSA B45 Series
- European Standard EN 232-2003 Baths
- IAPMO/UPC, cUPC



Colors

- 70 white
- Other refer to price book



Specific Model

Model #	Description	Color	
AK-603216-L	5' Apron Front Bath	☐ 70	☐ Other_____
AK-603216-R	5' Apron Front Bath	☐ 70	☐ Other_____
AK-603014-L	5' Apron Front Bath	☐ 70	☐ Other_____
AK-603014-R	5' Apron Front Bath	☐ 70	☐ Other_____

Product Specifications

AK-603216/AK-603014 The bath shall be made of SONG cast iron with Anti Slip basin finish. Product shall be 66"(168cm) in length, 34"(86.4cm) in width, and 16" (40.6cm) in height. Product shall feature an integral apron. Product shall be available with left or right drain. Bath shall be ADA compliant when installed per Section 607 of the Act. Bath shall be SONG Model AK-_____-____

APRON FRONT BATH
AK-603216, AK-603014

Technical Details *

Fixture	AK-603216	AK-603014
Basin Area Length	45" (114cm)	45" (114cm)
Basin Area width	23" (58cm)	22" (55.9cm)
Top Area Length	55" (140cm)	55" (140cm)
Top Area Width	25" (63.5cm)	24" (61cm)
Water Depth	10.6" (27cm)	8.6" (21.8 cm)
Capacity	39gal (147L)	33gal (124L)
Weight	353lbs (160kg)	316lbs (143kg)
Min. Floor Support	55lbs/sqft (268kg/sqm)	49lbs/sqft (240kg/sqm)

* All measurements are approximate and for comparison only.

Dimensions

A	32" (81.3cm)	30" (76.2cm)
B	60" (152.4cm)	60" (152.4cm)
C	16" (40.6cm)	14" (35.6cm)
D	16" (40.6)	15" (38 cm)
E	8.5" (21.6cm)	8.5" (21.6cm)
F	3" (7.6cm)	3" (7.6cm)
G	3.25" (8.2cm)	3.25" (8.2cm)

